



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Wednesday, September 17, 2014** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=1F250&Standard=061&>

NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. [Click here for a list of Abbreviations used in these Listings.](#)

Enecon Corporation

6 Platinum Court
Medford, NY 11763
United States
800-436-3266
516-349-0022

Facility : Medford, NY

Protective (Barrier) Materials

	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Trade Designation			

Coatings - Fittings

CHEMCLAD® XC[1] >= 6" CLD 23 EPOXY

[1] Colors: Light gray, white
 Number of Coats: 2 - 4
 Maximum Field Use Dry Film Thickness (in mils): 24
 Maximum Thinner: None
 Recoat Cure Time and Temperature: 4 hours at 77°F
 Final Cure Time and Temperature: 4 days at 77°F
 Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Pump

CHEMCLAD® XC[1] >= 4" CLD 23 EPOXY

[1] Colors: Light gray, white
 Number of Coats: 2 - 4
 Maximum Field Use Dry Film Thickness (in mils): 24
 Maximum Thinner: None
 Recoat Cure Time and Temperature: 4 hours at 77°F
 Final Cure Time and Temperature: 4 days at 77°F
 Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Tank

CHEMCLAD® XC[1] >= 1,500,000 gal. CLD 23 EPOXY

[1] Colors: Light gray, white
 Number of Coats: 2 - 4
 Maximum Field Use Dry Film Thickness (in mils): 24
 Maximum Thinner: None
 Recoat Cure Time and Temperature: 4 hours at 77°F
 Final Cure Time and Temperature: 4 days at 77°F
 Special Comments: Mix ratio of A:B is 5:3 by weight.

Coatings - Valve

CHEMCLAD® XC[1]

>= 6"

CLD 23

EPOXY

[1] Colors: Light gray, white

Number of Coats: 2 - 4

Maximum Field Use Dry Film Thickness (in mils): 24

Maximum Thinner: None

Recoat Cure Time and Temperature: 4 hours at 77°F

Final Cure Time and Temperature: 4 days at 77°F

Special Comments: Mix ratio of A:B is 5:3 by weight.

Number of matching Manufacturers is 1

Number of matching Products is 4

Processing time was 0 seconds