ELECON NEVVS





CeramAlloy CBX Outperforms Chromium Hard Facing At This Rock Crushing Mill In Texas

At this large rock crushing mill operation in Houston, Texas - the LARGEST producer of barium sulfate products in the world - 1.5 inch (37mm) barium ore is crushed into 0.0002 inch (5 microns) powder. As one might imagine, the abrasive wear on the mill components is very severe.

The plant engineers were looking for a more cost term solution to chromium Sales Director for the Gulf rock before it wears out and needs to be re-done.

Although skeptical, the plant engineers decided to try the CBX on one of the mill's plow bodies. This component is used to 'hurl' the rocks up to the crushing journals. After over 23,000 tons (46 MILLION lbs.) of rock. the CeramAlloy CBX was "still in great shape" according to the very surprised but also very pleased engineers at the plant.

The mill has now purchased additional CBX to protect the other plow bodies as well as various other components and they are very interested to see just how long the CeramAlloy CBX will ultimately last.









effective as well as longer hard face welding to protect the crusher components on their 66 inch Raymond Mill. They turned to ENECON's Coast Region for help. He suggested that they try CeramAlloy CBX to see if it would last longer than the chromium hard facing. The welding process is very expensive and time consuming and has a life expectancy of only about 10,000 tons of

700 Hicksville Road • ENECON Center Suite 110 • Bethpage, New York 11714 Toll Free: 888-4-ENECON • Phone: 516.349.0022 • Fax: 516.349.5522 Website: www.enecon.com • Email: info@enecon.com